

MIKALOR

ASFA

L (9 mm) - Black

The exclusive design of the housing keeps the screw in firm contact with the band at all times.

Designed for both manual and automated assembly.

Bevelled band edges to avoid the clip cutting into the hose.

All MIKALOR hose clips are marked with the application range, material, the MIKALOR logo and the country of manufacture in compliance with DIN 3017.

Cold formed stamped band thread which gives a very good grip as the raised thread is deeper than the thickness of the material used.

Smooth band underside which avoids damage to the hose.

Inner lip specially designed to guide the band end around the underside of the band. This feature help to avoid leaks and guarantees top performance compared to other clamps and an even distribution of pressure around the band.

100 % STAINLESS STEEL

250 hours salt spray test
(ASTM B-117)

ASFA

L (9 mm) - Black

FOR OUTER DIAMETERS (OD)
FROM **8 mm** UP TO **160 mm**

QUALITY

W3

Band, Housing and Screw:
Stainless steel - AISI 430
Finish: Delta Seal Black

Part Number	Ø Application (From / Up to)	Maximum Values	
		Pressure (BAR)	Torque (Nm)
73016011	8-16	45	3,0
73016020	12-22	45	3,0
73016038	16-27	42	3,5
73016046	20-32	36	3,5
73016062	25-40	32	4,0
73016070	30-45	28	4,0
73016089	32-50	24	4,0
73016095	40-60	19	4,0
73016100	50-70	17	4,0
73016118	60-80	15	4,0
73016126	70-90	13	4,0
73016134	80-100	11	4,0
73016142	90-110	10	4,0
73016150	100-120	9	4,0
73016169	110-130	8	4,0
73016177	120-140	7	4,0
73016185	130-150	6	4,0
73016193	140-160	5	4,0

This clamp is manufactured in AISI 430 with an additional matt-black surface treatment which increases its corrosion resistance. Thanks to the surface treatment, this clamp can be mounted discreetly in any application, making it a favourite in automotive or motorcycle applications.

The geometry, band, stamping, housing and screw are identical to other ASFA clamps, meaning that the performance is not altered in any way.

DIN 3017. The Black ASFA LW3 hose clip complies fully with the DIN 3017 norm and also with the directive EU 2002/95/EC.



BLACK ASFA-L PACKING:

200 units - Ø 8-16 up to Ø 20-32
100 units - Ø 25-40 up to Ø 60-80

50 units - Ø 70-90 up to Ø 80-100
25 units - Ø 90-110 up to 140-160

