



This clamp was designed for use in low and medium-pressure applications on assembly lines, due to its fast and easy locking system.

The design of the locking mechanism means that this clamp can be used in areas which are difficult to access. In this case, manual pliers can be used to mount the clip.

Another very important characteristic of this clamp is that, once it has been mounted, it is tamper-proof.

MATERIAL: Steel DIN 1.0935
FINISH: Galvanized
CORROSION RESISTANCE: 144 hours salt spray
ASTM B-117

Part Number	Ø A ±0.3	Ø B Closed	C ±0.5	D ±0.5	E ±0.1	F +0.4-0.1	G Max.	Box Quantity	Outer Box Quantity
03030752	10,0	8,3	8	2,6	0,6	7	14,0	1.000	4.000
03030760	13,3	10,8	8	2,6	0,6	7	17,5	1.000	4.000
03030779	15,7	13,2	8	2,8	0,6	7	19,9	1.000	4.000
03030787	17,5	14,3	8	2,8	0,8	7	22,5	1.000	4.000
03030795	17,8	14,6	8	2,8	0,8	7	22,5	1.000	4.000
03030808	18,5	15,3	8	2,8	0,8	7	23,5	1.000	4.000
03030816	20,5	17,3	8	2,8	0,8	7	26,0	500	2.000
03030824	29,5	26,3	8	2,8	0,8	7	35,5	500	2.000
03030832	31,6	28,4	8	2,8	0,8	7	37,5	500	2.000
03030840	39,6	36,4	8	2,8	0,8	7	45,5	500	500
03030859	40,5	37,3	8	2,8	0,8	7	46,5	500	500
03030867	45,5	42,3	8	2,8	0,8	7	51,5	200	800
03030875	47,0	43,8	8	2,8	0,8	7	53,0	200	1.600
03030883	51,5	48,3	8	2,8	0,8	7	57,5	100	800
03030891	52,5	49,3	8	2,8	0,8	7	58,5	100	800
03030904	65,5	62,3	8	2,8	0,8	7	71,5	100	800