



This washer is used in panel assembly using holes and groves which are much bigger than the diameter of the screw or bolt, in order to achieve evenly distributed pressure over the entire area of contact.

The ADD washer is also very useful when fastening two panels together.

Lateral movement can be avoided as the panels remain fixed in a static position.

The diameter of the washer chosen should be far greater than the diameter of the hole or groove in order to ensure sufficient contact area. The advantage of the use of the ADD washer is that the specific pressure is spread over a greater surface area in materials which are softer than steel.

MATERIAL: Spring steel
HARNESS: HV 425 ÷495 / HRC 43 ÷49
FINISH: Anti-rust oil-dipped

Part Number	d1	d2	S	Box Quantity	Outer Box Quantity
01060012	4,10 mín.	14,30 máx.	0,5 ± 0,03	1.000	16.000
01060020	5,10 mín.	17,30 máx.	0,5 ± 0,03	1.000	16.000
01060039	6,10 mín.	20,90 máx.	0,6 ± 0,03	1.000	8.000
01060055	8,12 mín.	23,50 máx.	0,8 ± 0,03	1.000	8.000
01060063	10,20 mín.	26,50 máx.	1,0 ± 0,03	1.000	8.000
01060071	12,50 mín.	31,50 máx.	1,1 ± 0,03	500	4.000