



This washer is used in assemblies involving aluminium, plastic parts or insulating material etc. It is also recommended for locking assemblies where there is danger of damage to a painted or enameled surface.

In electronics applications this washer is used to immobilize electrical contacts. Moderate tightening torque should be used with this washer.

MATERIAL: Spring steel
HARNESS: HV 416 ÷495 / HRC 42 ÷48
FINISH: Anti-rust oil-dipped

Ø Application mm	Part Number	d1	d2	h mín.	h max.	S	Box Quantity	Outer Box Quantity
2	01080010	2,20 +0,250-0	4,50 ± 0,375	0,50	1,00	0,30 ± 0,030	1.000	64.000
2,3	01080028	2,50 +0,250-0	5,00 ± 0,375	0,50	1,00	0,30 ± 0,030	7.000	112.000
2,5	01080036	2,80 +0,250-0	5,50 ± 0,375	0,55	1,10	0,30 ± 0,030	1.000	64.000
3	01080044	3,20 +0,300-0	6,00 ± 0,375	0,65	1,30	0,40 ± 0,050	5.000	80.000
3,5	01080052	3,70 +0,300-0	7,00 ± 0,450	0,70	1,40	0,40 ± 0,050	3.000	48.000
4	01080060	4,30 +0,300-0	8,00 ± 0,450	0,80	1,60	0,50 ± 0,050	1.000	64.000
5	01080079	5,30 +0,300-0	10,00 ± 0,450	0,90	1,80	0,50 ± 0,050	2.000	32.000
6	01080087	6,40 +0,360-0	11,00 ± 0,550	1,10	2,20	0,50 ± 0,050	1.250	20.000
7	01080095	7,40 +0,360-0	12,00 ± 0,550	1,20	2,40	0,50 ± 0,050	2.500	20.000
8	01080108	8,40 +0,360-0	15,00 ± 0,550	1,70	3,40	0,50 ± 0,060	1.250	20.000
10	01080116	10,50 +0,430-0	18,00 ± 0,550	2,00	4,00	0,80 ± 0,060	1.000	8.000