



The SRM push on fastener is a one-use fastener designed for use in assemblies which are not normally dismantled, as in order to do this it would be necessary to break the SRM. It is normally fitted to shafts with no groove but it can also be used with grooved shafts, which would help to improve its resistance to axial forces.

It is used in applications which do not require great force such as electrical devices, electricity, gas or water meters, measuring instruments, etc.

MATERIAL: Spring steel
CK67 (DIN 10132-4)

FINISH: Zinc-Plated Cr3

HARDNESS: HV 390 ÷ 485 / HRC 40 ÷ 48

Denomination	Part Number	d1 ±0.1	d	d2 ±0.3	d3 ±0.3	s	h +0.3 -0	Box Quantity	Outer Box Quantity	
SRRM2	02110370	2	1,75	+0,1-0	7,0	6,6	0,2	0,7	1.000	64.000
SRRM3	02110257	3	2,70	+0,1-0	7,3	6,7	0,3	0,8	1.000	64.000
SRRM4	02110388	4	3,70	+0,1-0	10,0	9,4	0,3	0,8	1.000	16.000
SRRM5	02110396	5	4,70	+0,1-0	11,0	10,2	0,3	0,9	1.000	16.000
SRRM6	02110409	6	5,70	+0,1-0	13,0	12,2	0,3	1,0	1.000	16.000
SRRM7	02110417	7	6,60	+0,1-0	14,0	13,2	0,3	1,0	1.000	16.000
SRRM8	02110425	8	7,70	+0,1-0	16,0	15,0	0,3	1,2	1.000	16.000
SRRM9	02110433	9	8,70	+0,1-0	17,0	16,0	0,3	1,4	1.000	16.000
SRRM10	02110281	10	9,60	+0,1-0	16,0	15,2	0,3	1,4	1.000	16.000
SRRM12	02110441	12	11,55	+0,15-0	22,0	20,8	0,4	1,4	500	8.000
SRRM14	02110450	14	13,55	+0,15-0	24,0	22,6	0,4	1,4	500	8.000