



The SRR Flat nut is a rectangular fastener with the entry orifice of the shaft situated in the middle. It is a one-use fastening element designed for use in assemblies which are not normally dismantled, as in order to do this it would be necessary to break the SRR.

It is used in applications which do not require great force such as electrical devices, electricity, gas or water meters, measuring instruments, etc.

MATERIAL: Spring steel
CK67 (DIN 10132-4)
FINISH: Anti-rust oil-dipped
HARDNESS: HV 422 ÷ 560 / HRC 43 ÷ 49

Denomination	Part Number	Ø d1 Application	Ø d +0.1	a ±0.3	b ±0.3	s ±0.03	x ±0.3	Box Quantity	Outer Box Quantity
SRR1,5	02110020	1,5	1,25	8	15	0,3	1,2	1.000	16.000
SRR2	02110038	2,0	1,75	8	15	0,3	1,2	1.000	16.000
SRR2,5	02110046	2,5	2,25	8	15	0,3	1,2	1.000	16.000
SRR3	02110054	3,0	2,70	8	15	0,3	1,4	1.000	16.000
SRR3,5	02110062	3,5	3,20	8	15	0,3	1,4	1.000	16.000
SRR4	02110070	4,0	3,70	10	18	0,4	1,8	1.000	16.000
SRR5	02110097	5,0	4,70	10	18	0,4	1,8	1.000	16.000
SRR6	02110118	6,0	5,70	12	18	0,4	1,8	1.000	8.000
SRR8	02110150	8,0	7,70	16	24	0,5	2,7	1.000	8.000