



Anchor designed to work with the polyamide nylon plug in a 14 mm diameter. Perfect for reinforced concrete, concrete, hollow concrete, autoclaved aerated concrete, solid brick, hollow brick, stone, etc. Its 24 mm diameter ring makes it possible to fix any element, even though it is widely used for scaffolds. There are extensions to fasten scaffolds to façades, with an end designed for this type of anchor.

MATERIAL: Polyamide 6
FINISH: Zinc plated

Denomination	Part Number	$\varnothing D$ ± 0.2	L ± 1	$\varnothing d$ ± 1	F ± 1	G ± 1	G ± 0.5	L1 ± 1	$\varnothing b$ 0 - 0.5	Box Quantity	Outer Box Quantity
ASN24-12095	09112010	12	95	24	65	75	30	65	11,9	25	100
ASN24-12120	09112028	12	120	24	65	75	30	65	11,9	25	100
ASN24-12160	09112036	12	160	24	65	75	30	65	11,9	25	100
ASN24-12190	09112044	12	190	24	65	75	30	65	11,9	25	100
ASN24-12230	09112052	12	230	24	65	75	30	65	11,9	25	100
ASN24-12300	09112060	12	300	24	65	75	30	65	11,9	10	60
ASN24-12350	09112079	12	350	24	65	75	30	65	11,9	10	60