



The standard nylon plug is made of 6.6 polyamide and is suitable for lightweight fastenings in solid materials such as concrete, stone, solid bricks. It has a washer that prevents the plug from being inserted too far into the drilled hole. Its side wings exert a friction in the hole that prevents the plug from rotating on itself when threading.

MATERIAL: Polyamide PA 6
APPLICATION: Concrete, brick, natural stone, sand stone

Size Ø D x L	Part Number	Ø D Drill	L Length	h1 min. Depth	Ø Bolt Application	Load Kn Recommended	Box Quantity	Outer Box Quantity
4 x 20	09110110	4	20	25	2 - 3	0,13	200	42.000
5 x 25	09110129	5	25	30	2,5 - 4	0,32	200	42.000
6 x 30	09110137	6	30	35	3,5 - 5	0,53	100	21.000
7 x 35	09110145	7	35	40	4 - 5,5	0,65	100	10.500
8 x 40	09110153	8	40	45	4,5 - 6	0,75	100	10.500
10 x 50	09110161	10	50	55	6 - 8	0,92	50	5.250
12 x 60	09110188	12	60	65	8 - 10	1,33	25	2.625
14 x 75	09110196	14	75	80	10 - 12	1,76	20	2.100
16 x 90	09110209	16	90	95	12	2,90	10	1.050