



The TX nylon plug is made of 6.6 polyamide and is suitable for use in solid (concrete, stone, brick...) and hollow materials (hollow brick, hollow concrete...) that support light loads. It has a countersunk collar that prevents the plug from being inserted too far into the hole and making its application complicated. It has undulations along its body to prevent it from rotating. Once screwed in, the plug bulges and expands, acquiring an oval shape that presses against the walls, in the case of solid material. In the case of hollow materials, the plug knots itself when expanding (nylon contracts creating a ball that prevents the plug from coming loose and fixes it).

MATERIAL: Polyamide PA 6
APPLICATION: Concrete, hollow and solid brick, natural stone, sand stone, plasterboard, papier-mâché

Size Ø D x L	Part Number	Ø D Drill	L Length	h1 min. Depth	Ø Bolt Application	Load Kn Recommended	Box Quantity	Outer Box Quantity
5 x 25	09110970	5	25	35	3 - 4	0,60	200	42.000
6 x 30	09110989	6	30	40	4 - 5	0,70	100	21.000
8 x 40	09110997	8	40	50	4,5 - 6	1,10	100	10.500
10 x 50	09111009	10	50	60	6 - 8	1,50	50	5.250
12 x 60	09111017	12	60	70	8 - 10	1,70	25	2.625