



The fact that these clamps are used on very small-bore hoses means that the material of the tube or hose can sometimes be very flexible, making it more difficult to ensure a leaktight assembly due to the possible deformation of the hose. In these cases, the inner-ring is key in helping to guarantee leaktightness as well as protecting the hose from being pinched during assembly.

**MATERIAL:** Clamp: Steel DC04 (EN 10130)

Inner-ring: Stainless steel AISI 301 1.4310 (10151)

**FINISH:** Clamp: Zinc plated Cr3

**CORROSION RESISTANCE:** Clamp: 72 hours salt spray (ASTM B-117)

Inner-ring: 250 hours salt spray (ASTM B-117)

Ø Application	Part Number	A ±0.2	B ±0.2	C ±0.2	D +0.5-0.2	F ±0.2	G ±0.2	E +0.1-0.02	Box Quantity	Outer Box Quantity
7.5-8.5	03011009	9,3	5,5	6,0	13,0	8,8	7,8	0,8	1.000	8.000
8.0-9.5	03011010	10,3	6,0	6,0	14,0	9,8	7,8	0,8	1.000	8.000
9.0-10.5	03011029	11,3	6,5	6,5	15,0	10,8	7,8	0,8	1.000	8.000
10.0-11.5	03011037	12,3	7,0	6,5	16,0	11,8	7,8	0,8	500	8.000
10.55-12.5	03011045	13,3	7,5	6,5	17,0	12,8	7,8	0,9	500	8.000
11.5-13.3	03011053	14,3	8,0	7,0	18,5	13,8	8,8	1,0	500	2.000
13.0-15.3	03011061	16,3	8,5	7,0	20,5	15,8	8,8	1,1	500	4.000
15.0-17.3	03011070	18,5	9,5	7,0	23,0	18,0	8,8	1,1	500	2.000