



With the aim of saving time and increasing productivity on the assembly line, Mikalor has developed the only clamp of its kind capable of guaranteeing the same tightening torque values and the same performance as a standard clamp.

Thanks to its exclusive design, the pre-assembly clip can be fitted to the clamp and later attached to the hose without any loss of functionality, tightening torque or reduction in performance. Another new feature of our pre-positioning system is that the clip can also be fixed to the hose using adhesive. This is the only pre-assembly system which guarantees that the hose is not damaged when the clamp is tightened.

**MATERIAL:** W3 - Steel AISI 430  
**FINISH:** Stainless steel  
**CORROSION RESISTANCE:** 200 hours salt spray (ASTM B-117)

\* Special dimensions and positioning of the clip according to customer requirements are available on request.

\* The maximum application pressure can vary depending on the type of hose used and the geometry of the coupling.

a	Ø Application mm	Part Number		Par (Bar)	Box Quantity
		Right	Left		
12	16-27	03059001	03061001	40	50
12	20-32	03059000	03061002	36	50
12	25-40	03059003	03061003	32	50
12	30-45	03059004	03061004	28	50
12	32-50	03059005	03061005	24	50
12	40-60	03059006	03061006	19	25
12	45-65	03059007	03061007	17	25
12	50-70	03059008	03061008	17	25
12	55-75	03059009	03061009	17	25
12	60-80	03059010	03061010	15	25
12	65-85	03059011	03061011	13	25
12	70-90	03059012	03061012	13	25
12	75-95	03059013	03061013	11	25
12	80-100	03059014	03061014	11	25