

VE-PLUS - Styrene-free vinylester chemical anchor



ETA	CE
Option 1 - 8-24 mm	
Option 7 - M8-M24	
Option 7 - 8-25 mm	
TR023 8-12 mm	
ETA-22/0760	
ETA-22/0757	



Styrene-free vinylester is the most versatile of all the resins in our range. It can be used with most materials (hollow brick, semi-solid brick, hollow brick, hollow concrete blocks, concrete, aerated concrete, cracked concrete and wood). It can take loads of up to 15000 kg in concrete and can also be used in surfaces covered in water. This resin is dielectric and is fire resistant for 120 minutes. This product can be used with corrugated rod. Certification for concrete with or without cracks CE Certificate Option 1.

USES:

- Cracked and non-cracked concrete
- All types of hollow materials
- Solid brick
- Masonry in general
- Wood or other high strength materials
- Use in immersed holes
- Valid for metric thread and rebar. Post-installation of rebar reinforcement
- Suitable for high crawl spaces

Content ml	Part Number	Nozzle of application	For dispensing tool	Duration months	Nozzle included	Minimum unit of sale	Outer Box Quantity
300	06000040	CA-00	PA-30 / PA30P / PE30 AN30 / AN40P	18	2	1	15
400	06000041	CA-00	PB40 / PB40P / AN40P	18	1	1	12