



Especially suitable for applications requiring tightening wires with rings, ropes with eyes, chains, etc.

The Hook/Hook turnbuckle provides for an instant assembly and quick tensioning.

TIPS: The quality of the finish guarantees a very good corrosion resistance. In order not to compromise safety, the SWL established for each size must never be exceeded.

MATERIAL: Steel C15
FINISH: Zinc plated

Thread size (Metric)	Denom.	Part Number	L	Ø	N	L1	Workload S.W.L (kg)	Box Quantity	Outer Box Quantity
M5	TGG105	09520650	70	7	35	56	60	50	400
M6	TGG106	09520669	110	8	55	77	70	50	300
M8	TGG108	09520677	110	10,5	57	85	140	25	150
M10	TGG110	09520685	125	13	68	106	220	25	75
M11	TGG111	09520693	125	15	68	110	260	25	25
M12	TGG112	09520706	125	16	70	117	310	10	50
M14	TGG114	09520714	140	18	75	124	450	10	40
M16	TGG116	09520722	170	20	88	144	600	10	10
M20	TGG120	09520730	200	21	105	170	910	5	5
M22	TGG122	09520749	220	24	118	200	1.100	1	25
M24	TGG124	09520757	255	26	135	215	1.300	1	30
M27	TGG127	09520765	255	34	135	240	1.600	1	20
M30	TGG130	09520773	255	34	135	240	2.100	1	10
M32	TGG132	09520781	295	38	148	260	2.150	1	1
M36	TGG136	09520790	295	46	160	275	2.300	1	6

These products are not PPE (Personal Protection Equipment)