



Bearing in mind that the thread at one end is clockwise and its opposite is counter-clockwise, the CTS turnbuckle body can be used with the whole range of ends depending on their sizes.

TIPS: Maximum performance and maximum safety can only be achieved when the CTS body is fitted with DIN 1480 ends made of steel of the same quality. The quality of the finish guarantees good corrosion resistance.

MATERIAL: Steel C15
FINISH: Zinc plated

Thread size (Metric)	Denom.	Part Number	D	E	F	L	L1	Workload S.W.L (kg)	Box Qty.	Outer Box Qty.
M5	CTS105	09521805	10	16,5	7	70	50	60	50	500
M6	CTS106	09521813	12	19	9	110	86	70	50	300
M8	CTS108	09521821	15	23	11	110	80	140	25	200
M10	CTS110	09521830	18	29	13	125	89	220	25	150
M11	CTS111	09521848	19	32	15	125	86	260	25	100
M12	CTS112	09521856	21	34	16	125	83	310	25	100
M14	CTS114	09521864	24	37	17	140	90	450	10	50
M16	CTS116	09521872	27	42	20	170	116	600	10	40
M20	CTS120	09521880	34	52	24	200	132	910	5	20
M22	CTS122	09521899	36	56	26	220	145	1.100	1	5
M24	CTS124	09521901	39	60	28	255	177	1.300	1	10
M27	CTS127	09521910	45	74	34	255	165	1.700	1	10
M30	CTS130	09521928	45	74	34	255	165	2.100	1	12
M32	CTS132	09521936	48	81	37	295	199	2.150	1	4
M36	CTS136	09521944	55	86	40	295	185	2.300	1	4

These products are not PPE (Personal Protection Equipment)