



Suitable for assembly on a DIN 1480 or DIN 1478 turnbuckle body and recommended for applications where the end to be fixed is a ring.

TIPS: The quality of the steel of the GTS hook guarantees performance and safety. The quality of the finish guarantees good corrosion resistance.

MATERIAL: Steel C15
FINISH: Zinc plated

Thread size (Metric)	Denom.	Part Number	B	L	L1	Workload S.W.L (kg)	Box Quantity	Outer Box Quantity
M5	GTS105	09522015	7	56	35	60	100	1.000
M6	GTS106	09522023	8	77	55	70	100	800
M8	GTS108	09522031	9,5	85	57	140	100	400
M10	GTS110	09522040	12	106	68	220	100	400
M11	GTS111	09522058	13	110	68	260	50	50
M12	GTS112	09522066	15	117	70	310	50	200
M14	GTS114	09522074	17	124	75	450	25	25
M16	GTS116	09522082	19	144	88	600	25	100
M20	GTS120	09522090	20	170	105	910	25	75
M22	GTS122	09522103	23	200	118	1.100	10	10
M24	GTS124	09522111	25	215	135	1.300	10	20
M27	GTS127	09522120	31	240	135	1.700	1	10
M30	GTS130	09522138	31	240	135	2.100	1	1
M32	GTS132	09522146	38	260	148	2.150	1	8
M36	GTS136	09522154	44	275	160	2.300	1	5