



Suitable for assembly on a DIN 1480 or DIN 1478 turnbuckle body and recommended for applications where the end to be fixed is a hook.

TIPS: The quality of the steel of the ring guarantees performance and safety. The quality of the finish guarantees good corrosion resistance.

MATERIAL: Steel C15
FINISH: Zinc plated

Thread size (Metric)	Denom.	Part Number	L	L1	Ø	D	Workload S.W.L (kg)	Box Quantity	Outer Box Quantity
M5	ATS105	09522218	57	35	8	16	60	100	2.000
M6	ATS106	09522226	80	55	9	20	70	100	1.000
M8	ATS108	09522234	85	57	10	22	140	100	600
M10	ATS110	09522242	105	68	14	31	220	50	300
M11	ATS111	09522250	108	68	15	33	260	50	200
M12	ATS112	09522269	111	70	16	35	310	50	200
M14	ATS114	09522277	124	75	18	40	450	25	100
M16	ATS116	09522285	150	88	22	47	600	25	100
M20	ATS120	09522293	168	105	24	52	910	10	60
M22	ATS122	09522306	190	118	28	60	1.100	10	10
M24	ATS124	09522314	212	135	28	65	1.300	10	10
M27	ATS127	09522322	224	135	31	71	1.700	1	15
M30	ATS130	09522330	224	135	31	71	2.100	1	10
M32	ATS132	09522349	245	148	36	88	2.150	1	1
M36	ATS136	09522357	277	158	38	94	2.900	1	5