


# DIN 582 lifting eye nut






The use of lifting eye nuts is especially recommended when the load to be lifted or lashed has a perfectly flat surface.

The lifting eye nut is joined to the unit to be lifted or lashed by bolting the eye to the unit via the threaded section thereby guaranteeing a perfect join between both parts and ensuring that the unit can be lifted or lashed safely.

**MATERIAL:** Steel C15
**FINISH:** Zinc plated

INSTRUCTIONS: In order not to compromise safety, the SWL working load of each metric bolt should never be exceeded.

| Thread size d1 | Denomination | Part Number | d2 | d3 | d4 | n | e | K | m | Workload Axial - W.L.L (kg) | Box Qty. | Outer Box Qty. |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| M6 | AEH106 | 09522816 | 36 | 20 | 20 | 36 | 8,5 | 8 | 10 | 90 | 100 | 400 |
| M8 | AEH108 | 09522824 | 36 | 20 | 20 | 36 | 8,5 | 8 | 10 | 140 | 100 | 400 |
| M10 | AEH110 | 09522832 | 45 | 25 | 25 | 45 | 10 | 10 | 12 | 230 | 100 | 300 |
| M12 | AEH112 | 09522840 | 54 | 30 | 30 | 53 | 11 | 12 | 14 | 340 | 100 | 100 |
| M14 | AEH114 | 09522859 | 63 | 35 | 35 | 62 | 13 | 14 | 16 | 500 | 50 | 50 |
| M16 | AEH116 | 09522867 | 63 | 35 | 35 | 62 | 13 | 14 | 16 | 700 | 50 | 50 |
| M18 | AEH118 | 09522875 | 72 | 40 | 40 | 71 | 16 | 16 | 19 | 930 | 50 | 50 |
| M20 | AEH120 | 09522883 | 72 | 40 | 40 | 71 | 16 | 16 | 19 | 1.200 | 50 | 50 |
| M22 | AEH122 | 09522891 | 81 | 45 | 45 | 80.5 | 18 | 18 | 21 | 1.500 | 25 | 25 |
| M24 | AEH124 | 09522904 | 90 | 50 | 50 | 90 | 20 | 20 | 24 | 1.800 | 25 | 25 |
| M27 | AEH127 | 09522912 | 96 | 53 | 55 | 97 | 22 | 21,5 | 25 | 2.500 | 10 | 10 |
| M30 | AEH130 | 09522920 | 108 | 60 | 65 | 109 | 25 | 24 | 28 | 3.600 | 10 | 10 |
| M36 | AEH136 | 09522939 | 126 | 70 | 75 | 128 | 30 | 28 | 32 | 5.100 | 1 | 4 |
| M42 | AEH142 | 09522947 | 144 | 80 | 85 | 147 | 35 | 32 | 38 | 7.000 | 1 | 4 |
| M48 | AEH148 | 09522955 | 166 | 90 | 100 | 168 | 40 | 38 | 46 | 8.600 | 1 | 1 |

These products are not PPE (Personal Protection Equipment)