



Thanks to the oval form of this lifting eye, it is suitable for use with all sorts of hooks, thereby ensuring that the unit can be lifted safely.

INSTRUCTIONS: In order not to compromise safety, the SWL working load of each metric bolt should never be exceeded.

MATERIAL: Steel Fe 430 B
FINISH: Black (uncoated oiled)

| Thread size D | Denomination | Part Number | A | B | C | E | F | G | L | Workload Axial - S.W.L. (kg) | Box Qty. | Outer Box Qty. |
|------------------|--------------|----------------|----|-----|-----|----|----|----|------|---------------------------------|-------------|-------------------|
| M8 | AE0108 | 09523018 | 18 | 34 | 24 | 10 | 8 | 19 | 43,5 | 80 | 50 | 200 |
| M10 | AE0110 | 09523026 | 24 | 44 | 30 | 14 | 10 | 28 | 58 | 160 | 50 | 80 |
| M12 | AE0112 | 09523034 | 30 | 56 | 34 | 16 | 13 | 32 | 72 | 250 | 50 | 50 |
| M14 | AE0114 | 09523042 | 30 | 56 | 34 | 16 | 13 | 32 | 72 | 320 | 25 | 25 |
| M16 | AE0116 | 09523050 | 36 | 68 | 40 | 20 | 16 | 38 | 86 | 400 | 20 | 20 |
| M18 | AE0118 | 09523069 | 36 | 68 | 40 | 20 | 16 | 38 | 86 | 510 | 25 | 25 |
| M20 | AE0120 | 09523077 | 42 | 80 | 48 | 24 | 19 | 45 | 100 | 630 | 10 | 10 |
| M22 | AE0122 | 09523085 | 42 | 80 | 48 | 24 | 19 | 45 | 100 | 800 | 10 | 10 |
| M24 | AE0124 | 09523093 | 50 | 94 | 56 | 28 | 22 | 53 | 119 | 1.000 | 10 | 10 |
| M27 | AE0127 | 09523106 | 50 | 94 | 56 | 28 | 22 | 53 | 119 | 1.250 | 5 | 5 |
| M30 | AE0130 | 09523114 | 60 | 112 | 68 | 36 | 26 | 64 | 141 | 1.600 | 5 | 5 |
| M36 | AE0136 | 09523122 | 70 | 128 | 80 | 42 | 29 | 75 | 164 | 2.500 | 1 | 1 |
| M42 | AE0142 | 09523130 | 82 | 148 | 92 | 50 | 33 | 87 | 192 | 3.750 | 1 | 1 |
| M48 | AE0148 | 09523149 | 90 | 162 | 105 | 58 | 36 | 99 | 211 | 5.000 | 1 | 1 |