



The D-shackle is the lifting device most frequently used as an intermediate part between a ring, eyebolt or hook and a sling.

The square design of the pin head is difficult to tamper if required for the lifting structure for safety purposes.

TIPS: For correct assembly, the hook must always be attached to the shackle bolt and the sling, the wire or rope must

**MATERIAL:** Steel C15  
**FINISH:** Zinc plated

be attached to the shackle bow. Assembly must never be carried out in reverse order. In order not to compromise safety, the SWL established for each size must never be exceeded.

Size D	Denomination	Part Number	d	B	H	C	M	Workload W.L.L (kg)	Box Quantity	Outer Box Quantity
5	GRCC105	09527406	5	10	19	10	M5	80	50	800
6	GRCC106	09527414	6	12	24	12	M6	100	50	400
8	GRCC108	09527422	8	16	32	16	M8	200	50	300
10	GRCC110	09527430	10	20	40	19	M10	320	50	150
11	GRCC111	09527449	11	22	44	21	M11	400	25	150
12	GRCC112	09527457	12	25	48	24	M12	520	25	100
14	GRCC114	09527465	14	28	56	27	M14	650	25	75
16	GRCC116	09527473	16	32	64	31	M16	800	10	40
19	GRCC119	09527490	19	38	76	38	M20	1.100	5	20
22	GRCC122	09527502	22	44	85	43	M22	1.500	1	8
25	GRCC125	09527510	25	50	95	49	M24	2.100	1	8