



It is the most functional, economical, fast and practical element for making connections with objects generally intended to be hung.

Its perfect S shape and the length proportional to the corresponding thickness guarantee excellent application safety.

TIPS: Galvanised S-hooks are not suitable for heavy working loads. The quality of the coating guarantees good corrosion resistance.

MATERIAL: Steel C15
FINISH: Zinc plated

| Ø Size D | Denomination | Part Number | B | A | C | Workload W.L.L (kg) | Box Quantity | Outer Box Quantity |
|----------|--------------|-------------|----|-----|-----|---------------------|--------------|--------------------|
| 3 | ESE 103 | 09528601 | 7 | 25 | 3,5 | 7 | 200 | 4000 |
| 3,5 | ESE 103,5 | 09528610 | 9 | 30 | 4 | 15 | 200 | 4000 |
| 4 | ESE 104 | 09528628 | 11 | 35 | 5 | 20 | 200 | 2000 |
| 4,5 | ESE 104,5 | 09528636 | 12 | 40 | 5 | 25 | 200 | 2000 |
| 5 | ESE 105 | 09528644 | 14 | 45 | 5,5 | 30 | 200 | 800 |
| 6 | ESE 106 | 09528652 | 16 | 55 | 7 | 50 | 100 | 600 |
| 7 | ESE 107 | 09528660 | 20 | 65 | 7,5 | 70 | 50 | 400 |
| 8 | ESE 108 | 09528679 | 23 | 75 | 8,5 | 130 | 50 | 200 |
| 9 | ESE 109 | 09528687 | 24 | 90 | 11 | 150 | 25 | 150 |
| 10 | ESE 110 | 09528695 | 25 | 103 | 13 | 180 | 25 | 100 |

These products are not PPE (Personal Protection Equipment)