



Thanks to the exclusive design of the housing and the high-strength screw, the ASFA L Worm-Drive Clip has excellent performance while being at the same time very compact.

The cold-formed stamped 9 mm band, smoothed on the underside, combined with the bevelled band edges protects the hose from any damage.

DIN 3017. The ASFA L hose clip complies fully with the DIN 3017 norm and also with the directive EU 2002/95/EC.

MATERIAL: Band and support: W1 Galvanized steel DIN 1.0935
Bolt: Steel Qst 36-3 DIN 1.0214

FINISH: Bolt: Zinc plated Cr3

CORROSION RESISTANCE: 144 hours salt spray (ASTM B-117)

Ø Application mm	Part Number	L +1-0.5	T ±0.1	H Max.	B Max.	S Min.	Max. Pressure Bar	Box Quantity	Outer Box Quantity
8-12 (*)	03008745	18,5	0,65	9,2	11,5	15,0	15	200	1.600
8-16	03008753	22,1	0,65	10,5	14,0	15,0	45	200	800
12-22	03008761	22,1	0,65	10,5	14,0	15,0	45	200	800
16-27	03008770	23,6	0,75	10,5	14,0	16,5	42	200	800
20-32	03008788	23,6	0,75	10,5	14,0	16,5	36	200	800
25-40	03008796	25,6	0,75	10,5	14,0	17,1	32	100	400
30-45	03008809	25,6	0,75	10,5	14,0	17,1	28	100	800
32-50	03008817	25,6	0,75	10,5	14,0	17,1	24	100	800
40-60	03008825	25,6	0,75	10,5	14,0	17,1	19	100	400
50-70	03008833	29,6	0,75	10,5	14,0	21,1	17	100	100
60-80	03008841	29,6	0,75	10,5	14,0	21,1	15	100	100
70-90	03008850	29,6	0,75	10,5	14,0	21,1	13	50	400
80-100	03008868	29,6	0,75	10,5	14,0	21,1	11	50	50
90-110	03008876	29,6	0,75	10,5	14,0	21,1	10	25	200
100-120	03008884	29,6	0,75	10,5	14,0	21,1	9	25	200
110-130	03008892	29,6	0,75	10,5	14,0	21,1	8	25	25
120-140	03008905	29,6	0,75	10,5	14,0	21,1	7	25	25
130-150	03008913	29,6	0,75	10,5	14,0	21,1	6	25	25
140-160	03008921	29,6	0,75	10,5	14,0	21,1	5	25	25

(*) ASFA-L 7 mm