



This system guarantees that the correct torque is applied to a clamp thanks to a torque cap which is fitted to the screw of the standard clamp. When the target torque is reached, the tip of the torque cap breaks off, making it impossible to apply more torque. The remains of the torque cap can then be left in place, making it impossible to apply more torque, or removed if more torque is required. These clamps are supplied with the torque cap in place and ready to be assembled.

MATERIAL: Galvanised steel clamp W1
ZAMAK 5 GD-ZnALU steel
cap Cu1 silver grey

CORROSION RESISTANCE: 144 hours salt spray
ASTM B-117

Ø Application	Part Number	A	B	C	ØD	Box Quantity
16-27	CA3009001	10,8	2,4	7	11	50
20-32	CA3009002	10,8	2,4	7	11	50
25-40	CA3009003	10,8	2,4	7	11	50
30-45	CA3009004	10,8	2,4	7	11	50
32-50	CA3009005	10,8	2,4	7	11	50
40-60	CA3009006	10,8	2,4	7	11	50
50-70	CA3009007	10,8	2,4	7	11	50
60-80	CA3009008	10,8	2,4	7	11	50
70-90	CA3009009	10,8	2,4	7	11	50
80-100	CA3009010	10,8	2,4	7	11	25
90-110	CA3009011	10,8	2,4	7	11	25
100-120	CA3009012	10,8	2,4	7	11	25
110-130	CA3009013	10,8	2,4	7	11	25
120-140	CA3009014	10,8	2,4	7	11	25
130-150	CA3009015	10,8	2,4	7	11	25
140-160	CA3009016	10,8	2,4	7	11	25
150-170	CA3009017	10,8	2,4	7	11	25
160-180	CA3009018	10,8	2,4	7	11	25
170-190	CA3009019	10,8	2,4	7	11	10
180-200	CA3009020	10,8	2,4	7	11	10
190-210	CA3009021	10,8	2,4	7	11	10
200-220	CA3009022	10,8	2,4	7	11	10
210-230	CA3009023	10,8	2,4	7	11	10
220-240	CA3009024	10,8	2,4	7	11	10