
MIKALOR

Bridge Clamp ASFA S (12 mm)





ASFA S Bridge Clamp with 12 mm bandwidth and manufactured with one or two bridges are an ideal solution for hoses with an outer helix. The geometry and design of the bridges ensure a leaktight fit. These clamps are specially recommended for use on medium-sized and large bore hose mainly used for ventilation or extraction.

* The maximum application pressure can vary depending on the type of hose used and the geometry of the coupling.


MATERIAL:	Available in: W1 - galvanized W2 - AISI 430 W3 - AISI 430 W4 - AISI 304 W5 - AISI 316
FINISH:	W1: Zinc plated W2 / W3 / W4 / W5:
CORROSION RESISTANCE:	Stainless steel According to the material


Ø Application mm	**Number of bridges**	**Bridge location**	**S** +0.10	**h** Máx.	**a** +0.3 **a** -0.2	**b** Max.	**Pressure (Bar)**	**Box Quantity**
32-50	1-2	right/left	0,85	11	12	16,7	32	50
40-60	1-2	right/left	0,85	11	12	16,7	28	50
50-70	1-2	right/left	0,85	11	12	16,7	23	50
60-80	1-2	right/left	0,85	11	12	16,7	18	50
70-90	1-2	right/left	0,85	11	12	16,7	15	50
80-100	1-2	right/left	0,85	11	12	16,7	12	25
90-110	1-2	right/left	0,85	11	12	16,7	10	25
100-120	1-2	right/left	0,85	11	12	16,7	9	25

MIKALOR

Bridge Clamp ASFA S (12 mm)







Ø Application mm	**Number of bridges**	**Bridge location**	**S** +0.10	**h** Máx.	**a** +0.3 **a** -0.2	**b** Max.	**Pressure (Bar)**	**Box Quantity**
110-130	1-2	right/left	0,85	11	12	16,7	8	25
120-140	1-2	right/left	0,85	11	12	16,7	7	25
130-150	1-2	right/left	0,85	11	12	16,7	6	25
140-160	1-2	right/left	0,85	11	12	16,7	5	25
150-170	1-2	right/left	0,85	11	12	16,7	4	25
160-180	1-2	right/left	0,85	11	12	16,7	3	25
170-190	1-2	right/left	0,85	11	12	16,7	2	10
180-200	1-2	right/left	0,85	11	12	16,7	2	10
190-210	1-2	right/left	0,85	11	12	16,7	1,8	10
200-220	1-2	right/left	0,85	11	12	16,7	1,8	10
210-230	1-2	right/left	0,85	11	12	16,7	1,6	10
220-240	1-2	right/left	0,85	11	12	16,7	1,6	10