



With the aim of minimising costs on the assembly line, particularly in the automotive sector, Mikalor has developed an ASFA clamp incorporating a pre-positioning notch in the band. This clamp works at the same tightening torque and guarantees the same performance as the standard range.

The position of the notch in the band matches exactly that of the counter part in the assembly, allowing the clamp to be safely and accurately pre-positioned for tightening when required. Moreover, the notch can be located in the most suitable place in the band for final assembly.

**MATERIAL:** W4 - Steel AISI 304  
**FINISH:** Stainless steel  
**CORROSION RESISTANCE:** 400 hours salt spray (ASTM B-117)

\* Design, number of notches and position according to customer specifications.

\* The maximum application pressure can vary depending on the type of hose used and the geometry of the coupling.

a	Ø Application mm	Part Number	L	S +0.1	H Max.	b Max.	Par (Bar)	Box Quantity
12	25-40	PDT2540TAL-W4S	29,6	0,85	11	16,7	40	50
12	30-45	PDT3045TAL-W4S	29,6	0,85	11	16,7	35	50
12	32-50	PDT325TAL-W4S	29,6	0,85	11	16,7	35	50
12	40-60	PDT4060TAL-W4S	29,6	0,85	11	16,7	30	50
12	50-70	PDT5070TAL-W4S	29,6	0,85	11	16,7	25	50
12	60-80	PDT6080TAL-W4S	29,6	0,85	11	16,7	20	50
12	70-90	PDT7090TAL-W4S	29,6	0,85	11	16,7	17	50
12	80-100	PDT80100TAL-W4S	29,6	0,85	11	16,7	14	25
12	90-110	PDT90110TAL-W4S	29,6	0,85	11	16,7	12	25
12	100-120	PDT100120TAL-W4S	29,6	0,85	11	16,7	10	25
12	110-130	PDT110130TAL-W4S	34,6	0,85	11	16,7	8	25
12	120-140	PDT120140TAL-W4S	34,6	0,85	11	16,7	7	25
12	130-150	PDT130150TAL-W4S	34,6	0,85	11	16,7	6	25
12	140-160	PDT140160TAL-W4S	34,6	0,85	11	16,7	5	25