



Aluminum ferrules are specially designed for the connection of steel cable and are suitable for the permanent fastening of the cable, since it is a non-reusable product. In addition, some of the smaller dimensions help to achieve discreet splices. Manufactured in aluminum, these ferrules comply with the EN 13411-3 standard and avoid corrosion and deterioration due to use, maintaining optimum, long-lasting resistance.

MATERIAL: Aluminium
STANDARD: EN 12411-3

Part Number	Wire rope Ø mm	A mm	B mm	S mm	L mm	Weight kg / 1.000 ud.	Box Quantity	Outer Box Quantity
09226001	1,0	1,2	2,4	0,65	5	0,098	200	15.000
09226012	1,5	1,7	3,4	0,75	6	0,176	200	10.000
09226023	2,0	2,2	4,4	0,85	7	0,285	200	15.000
09226034	2,5	2,7	5,4	1,05	9	0,439	200	10.000
09226045	3,0	3,3	6,6	1,25	11	0,907	200	10.000
09226056	3,5	3,8	7,6	1,50	13	1,180	200	5.000
09226067	4,0	4,4	8,8	1,70	14	1,630	100	5.000
09226089	5,0	5,5	11,0	2,10	18	3,620	100	2.500
09226090	6,0	6,6	13,2	2,50	21	5,870	50	1.250
09226123	8,0	8,8	17,6	3,30	28	12,960	50	500