
# Zinc-Plated DIN 5685/A Chain






DIN 5685/A zinc-plated chain, the standard of which indicates the ratio of link, pitch and width is suitable for traction, towing, marking and signalling tasks and its zinc-plating process protects the steel from corrosive agents.

**MATERIAL:** Q235 Grade 30 steel
**FINISH:** Zinc-plated

## Packing: box with window

| Part Number | Nominal dimension | Ød mm | t mm | b mm | Workload N | Test load N | Breaking load N | Weight kg / metre | Packing metre / box |
|---|---|---|---|---|---|---|---|---|---|
| 09300052 | 2,0 | 2,0 | 12 | 8 | 250 | 500 | 1.250 | 0,07 | 60 |
| 09300055 | 2,5 | 2,5 | 14 | 10 | 375 | 750 | 2.000 | 0,10 | 60 |
| 09300058 | 3,0 | 3,0 | 16 | 12 | 560 | 1.120 | 2.800 | 0,15 | 60 |
| 09300061 | 4,0 | 4,0 | 19 | 16 | 1.000 | 2.000 | 5.000 | 0,30 | 50 |
| 09300064 | 5,0 | 5,0 | 21 | 20 | 1.575 | 3.250 | 7.750 | 0,50 | 30 |
| 09300067 | 6,0 | 6,0 | 24 | 24 | 2.250 | 4.500 | 11.500 | 0,70 | 30 |
| 09300070 | 7,0 | 7,0 | 28 | 28 | 3.000 | 6.000 | 15.000 | 1,00 | 25 |
| 09300073 | 8,0 | 8,0 | 32 | 32 | 4.000 | 8.000 | 20.000 | 1,30 | 20 |
| 09300076 | 9,0 | 9,0 | 36 | 36 | 5.000 | 10.000 | 25.000 | 1,60 | 15 |
| 09300079 | 10,0 | 10,0 | 40 | 40 | 6.250 | 12.500 | 31.000 | 2,05 | 10 |
| 09300082 | 12,0 | 12,0 | 48 | 48 | 9.000 | 18.000 | 45.000 | 2,85 | 8 |
| 09300085 | 14,0 | 14,0 | 56 | 56 | 18.400 | 36.800 | 92.000 | 3,80 | 6 |
| 09300088 | 16,0 | 16,0 | 64 | 56 | 24.000 | 48.000 | 12.000 | 5,40 | 5 |