



DIN 5685/A zinc-plated chain, the standard of which indicates the ratio of link, pitch and width is suitable for traction, towing, marking and signalling tasks and its zinc-plating process protects the steel from corrosive agents.

MATERIAL: Q235 Grade 30 steel
FINISH: Zinc-plated

Packing: box with window

Part Number	Nominal dimension	Ød mm	t mm	b mm	Workload N	Test load N	Breaking load N	Weight kg / metre	Packing metre / box
09300052	2,0	2,0	12	8	250	500	1.250	0,07	60
09300055	2,5	2,5	14	10	375	750	2.000	0,10	60
09300058	3,0	3,0	16	12	560	1.120	2.800	0,15	60
09300061	4,0	4,0	19	16	1.000	2.000	5.000	0,30	50
09300064	5,0	5,0	21	20	1.575	3.250	7.750	0,50	30
09300067	6,0	6,0	24	24	2.250	4.500	11.500	0,70	30
09300070	7,0	7,0	28	28	3.000	6.000	15.000	1,00	25
09300073	8,0	8,0	32	32	4.000	8.000	20.000	1,30	20
09300076	9,0	9,0	36	36	5.000	10.000	25.000	1,60	15
09300079	10,0	10,0	40	40	6.250	12.500	31.000	2,05	10
09300082	12,0	12,0	48	48	9.000	18.000	45.000	2,85	8
09300085	14,0	14,0	56	56	18.400	36.800	92.000	3,80	6
09300088	16,0	16,0	64	64	24.000	48.000	12.000	5,40	5